

# Agriculture & Food

A complete range of rubber hoses and assemblies for liquid and solid food products transfer, **without phthalates** and complying with the most stringent requirements for contact with foodstuffs products (European legislations and FDA).

## GUARANTEE HYGIENE, SAFETY, RELIABILITY

**Food:** Milk collection/Food transfer/Cleaning/Bulk tank truck discharge

**Agriculture:** Spraying/Fish farm

### Food range

Applications	Product name	Diameter range (mm)	WP (bar)	Max. vacuum (bar)	Temp. (°C)	
<b>Milk collection</b>						
	<b>LACTADIAL</b>		51 - 76	6	0.7	- 30 to + 80 °C
	<b>CITERDIAL</b>		25 - 150	6	0.9	- 30 to + 80 °C
<b>Food transfer</b>						
	<b>CITERDIAL</b>		25 - 150	6	0.9	- 30 to + 80 °C
	<b>ALIKLER G2</b>		25 - 150	10	0.9	- 30 to + 100 °C
	<b>ALIKLER D</b>		32 - 100	15	0.7	- 30 to + 100 °C
	<b>MILLESIME</b>		25 - 150	10	0.9	- 30 to + 100 °C
	<b>TRELLVIN</b>		38 - 63	10	0.7	- 30 to + 100 °C
	<b>TRELLVIN L</b>		75 - 150	10	-	- 30 to + 100 °C
	<b>ALCODIAL</b>		25 - 76	6	0.9	- 30 to + 80 °C
	<b>VINITRELL</b>		38 - 75	10	0.9	- 30 to + 80 °C
	<b>VENDANGE</b>		100 - 150	6	-	- 30 to + 80 °C
<b>Cleaning</b>						
	<b>KLENET</b>		13 - 25	10	-	- 20 to + 95 °C
	<b>BIOCLEAN</b>		7.9 - 15.9	60	-	- 20 to + 100 °C
	<b>BIOVAST</b>		13 - 25	20 Steam 6 bar	-	- 20 to + 100 °C Steam 165 °C
	<b>BERGALAV</b>		10 - 25	10 Steam 6 bar	-	- 30 to + 160 °C Steam 165 °C
	<b>TRELLJET 681</b> ANTIMICROBIAL PROTECTION		9.5 - 12.7	200	-	- 40 to + 120 °C
<b>Bulk tank truck discharge</b>						
	<b>SUPERVRAC AL EC</b>		75 - 125	7	-	- 30 to + 80 °C
<b>Agriculture range</b>						
<b>Spraying</b>						
	<b>ALTIPLUS</b>		8 - 25	60/40	-	- 30 to + 70 °C
	<b>PULVEDUC</b>		8 - 25	60/40	-	- 30 to + 70 °C
<b>Fish farm</b>						
	<b>FP 2007</b> <b>FP 3010</b>		254 - 457	2/3	-	- 40 to + 80 °C



### Advantages of the crimped solution



- No retention area, preventing bacterial growth ⇔ crimping guarantees smoothness hose/coupling
- No risk of disconnection ⇔ no risk of product loss
- Elimination of prominent parts ⇔ safe and easy handling

