



Eau/Water

Usage courant - Refoulement - Aspiration - Refroidissement - Applications spéciales

General applications - Discharge applications - Suction applications - Cooling systems - Special applications

Famille d'application Application	Tuyaux et flexibles - Points particuliers Hoses and assemblies - Specific informations	Nature du tube Inner tube	Revêtement Cover	PS WP (bar)	Temp. Temp. (°C)	Diamètre intérieur (de/à) ID (from/to) (mm)
Usage courant/General applications						
	CRISAL AL	PVC	PVC	15 - 6	+ 60	6 50
	RED WATER arrosage/watering	SBR	SBR	10	+ 70	13 152
	CASCADE arrosage, eau chaude watering, hot water	EPDM	EPDM	10	+ 100	12.7 25.4
Refoulement/Discharge applications						
	STARKLER industrie, applications sévères industry, tough conditions	EPDM	EPDM	20 - 10	+ 100	12.7 38
	COLORADO S industrie, applications sévères, aplatisable/industry, tough conditions, lay-flat	EPDM	EPDM	10 - 5	+ 100	40 120
	AQUAKLER 15 irrigation, aplatisable irrigation equipment, lay-flat	SBR/NR	SBR/NR	15 - 8	+ 70	40 254
	AP Bleu aplatisable PVC/PVC lay-flat	PVC	PVC	13 - 3	+ 40	19 200
	AP Rouge aplatisable PVC/PVC lay-flat	PVC	PVC	16 - 7	+ 40	35 150
Aspiration/Suction applications						
	OSS IV tuyau à manchettes cuffed-ends hose	NR	NR	5 - 3	+ 60	25 200
	OSM II lisse, tronçnable, hélice PET smooth, easy to cut	SBR	SBR	5	+ 60	20 100
	OST applications sévères/tough applications	SBR	SBR	10	+ 60	25 152
	OST EPDM 16 BAR applications sévères tough applications	EPDM	EPDM	16	+ 120	25.4 152.4
	OSL joc gris PVC/grey PVC helix	PVC	PVC	10 - 4	+ 60	20 120
	OSX spire acier/steel helix	PVC	PVC	7 - 2	+ 50	20 150
Refroidissement/Cooling systems						
	KLERHEAT	EPDM	fibre de verre fiber glass EPDM	10	+ 100	13 50
Applications spéciales/Special applications						
	BOAT SANITARY HOSE eaux usées bateaux boat waste water	Butyl (IIR)	EPDM	10	+ 100	16 38



Eau : nettoyage haute pression / Water: high pressure jetting

Famille d'application Application	Tuyaux et flexibles - Points particuliers Hoses and assemblies - Specific informations	Nature du tube Inner tube	Revêtement Cover	PS WP (bar)	Temp. Temp. (°C)	Diamètre intérieur (de/à) ID (from/to) (mm)
Nettoyage haute pression/High pressure jetting						
	TRELLJET 560 2 nappes acier/2 steel carcass	NBR/SBR	SBR/NBR	650	+ 150	7.9 9.5
	TRELLJET 561 1 nappe acier/1 steel carcass	NBR/SBR	SBR/NBR	400 - 350	+ 150	6.4 12.7
	TRELLJET 580 2 nappes acier, agroalimentaire 2 steel carcass, food grade	NBR/SBR	SBR/NBR	650 - 500	+ 150	7.9 12.7
	TRELLJET 581 1 nappe acier, agroalimentaire 1 steel carcass, food grade	NBR/SBR	SBR/NBR	400 - 350	+ 150	6.4 12.7